



Rec'd PCT/PTO 15 MAR 2005

PG/GB 2003 / 001125
10/527887



#2

INVESTOR IN PEOPLE

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 17 APR 2003

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *[Signature]*

Dated 4 April 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)16SEP02 E748416-1 D01891
P01/7700 0.00-0221391.6

The Patent Office

Curdiff Road
Newport
Gwent NP9 1RH

Request for grant of a patent
(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

P1335

2. Patent application number
(The Patent Office will fill in this part)

0221391.6

16 SEP 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

THE SECRETARY OF STATE FOR DEFENCE
DSTL
Porton Down
Salisbury, Wiltshire.
SP4 0JQ, UK

Patents ADP number (if you know it)

699 767 0005

If the applicant is a corporate body, give the country/state of its incorporation

GB

4. Title of the invention

APPARATUS FOR DIRECTING PARTICLES IN A FLUID

5. Name of your agent (if you have one)

Skelton, Stephen Richard

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)

D/IPR Formalities Section
Poplar 2
MoD Abbey Wood #2218
Bristol
BS34 8JH

8 28140 4001

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 3

Claim(s) 3

Abstract 1

Drawing(s) 5

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) One.

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I / We request the grant of a patent on the basis of this application.

Date 16/9/02

Signature

SSkelton

SR SKELTON

12. Name and daytime telephone number of person to contact in the United Kingdom

Mrs J M Northcott 0117 91 32860

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent of the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

a) If you need help to fill in this form or have any questions, please contact the Patent Office on 0645 500505.

b) Write your answers in capital letters using black ink or you may type them.

c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.

d) If you have attached 'Yes' Patents Form 7/77 will need to be filed.

e) Once you have filled in the form you must remember to sign and date it.

f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

DUPLICATE

- 1 -

APPARATUS FOR DIRECTING PARTICLES IN A FLUID

INTRODUCTION

When an ultrasound standing wave is created in a suspension of particles a force is exerted on the particles either towards the pressure nodes or the antinodes. For example, bacteria in an aqueous suspension move towards the pressure nodes. This is because the mass density and the speed of sound in the cells are greater than the respective values of the medium. In contrast, oil droplets or air bubbles dispersed in water move towards the pressure antinodes, because their density and speed of sound are lower than for the medium. The magnitude and direction of these acoustic radiation forces have been discussed elsewhere (King, 1934; Yosioke and Kawasima, 1955; Gorkov, 1962; Nyborg, 1967; Crum, 1971; Gould and Coakley, 1974; Whitworth and Coakley, 1992; Gröschl, 1998). The subject of this paper is the position of nodes within the chamber itself. This is of particular importance for the development of short pathlength chambers that contain a single node (Johnson and Fekke, 1995; Hawkes and Coakley, 2001; Hawkes et al., 2002). The Reynolds number is very low for such short pathlength chambers (e.g. 1.1 for a 0.25 mm chamber with an average flow velocity of 60 mm/s) with laminar flow conditions throughout the chamber. Two applications for these systems currently under development are: 1) a particle filter consisting of a chamber with a region of standing wave radiation where particles are moved to a central nodal position, followed by a region which takes advantage of the laminar flow where the clear medium on either side of the central particles is drawn away (Hawkes et al., 2002; Hawkes and Coakley, 2001); 2) a system to enhance the particle capture rate of biosensor surfaces by driving particles to the wall of the chamber (unpublished).

The aim of this paper is to describe fundamental design criteria, which must be applied for the development of any ultrasound system where node positioning is required. Four positions where the node can be placed between two chamber walls will be considered, these are against the transducer wall, centrally between the walls, against the reflector wall and against both walls. The method for calculating the node positions is based on the transfer matrix multilayer model. The reliability of this model was tested previously (Hawkes et al., 2002), here it is used as a design tool.

Table 1 Material properties

	Piezoceramic A	Steel B, D	Water C
Speed of sound [m/s]	4080	6100	1500
Mass density [kg/m ³]	7700	7800	1000
Acoustic quality factor	1000	1000	1000
Dielectric constant [F/m]	1.2×10^{-8}		
Tangent of dielectric loss angle	3.0×10^{-3}		
Electromechanical coupling factor	0.48		
Electrode area [mm ²]	200		
Thickness $Q = \lambda/4$ (@ 3 MHz) [mm]		0.508	0.125
Thickness $H = \lambda/2$ (@ 3 MHz) [mm]	0.680	1.016	0.250

- 2 -

SIMULATION CHOICES

A model (Nowotny and Benes, 1987; Nowotny et al., 1991) to simulate acoustic wave propagation through a multilayer system is used. This transfer matrix/multilayer model has recently been experimentally validated in detail (Hawkes et al., 2002; Gröschl, 1998). Here the model has been run using data and construction details similar to those used for the experimental verification (Hawkes et al., 2002), see Figure 1. The ultrasound is produced by a piezoceramic layer (A), transmitted to the water layer (C) through stainless steel (B) and reflected by a second layer of stainless steel (D). The relevant properties of these layers are given in Table 1. The aim here is to describe general design principles. For this purpose we choose a fundamental frequency of 3 MHz and acoustic quality factors of 1000 for the different layers (previous fitted quality factor results were 150 and 350 for water and the piezoceramic respectively, while data for pure water is more than 10,000 and manufacturer data for the piezoceramic is 1000). Furthermore, the glue layer to fix the ceramic to the transmission layer is not considered here. The thicknesses of the transmission and reflector layers are modelled with values which at 3 MHz are exactly $\lambda/2$, $\lambda/4$ and 0 and for water $\lambda/2$ and $\lambda/4$. The corresponding dimensions in mm are given in the last two rows of Table 1. These $\lambda/4$ steps represent the extremes for the node positions. Results will be very similar for systems with thicker layers. For example, a $\lambda/4$ layer will behave in a similar manner to $3\lambda/4$, $5\lambda/4$ etc layers, and a $\lambda/2$ layer will behave in a similar manner to λ , $3\lambda/2$ etc layers. Increasing the number of wavelengths in a system will alter frequency spectra bringing the peaks closer together.

Construction codes

The large numbers of constructions considered here are referred by the thickness values of the component layers in terms of wavelength at 3 MHz: 0 = no layer, Q = $\lambda/4$, H = $\lambda/2$. The piezoceramic layer is modelled with constant thickness of $\lambda/2$ and is not included in the code. The passive layers are described by three letters, OHQ for example refers to a construction with no transmission layer, $\lambda/2$ water layer (0.25 mm) and $\lambda/4$ stainless steel reflector (0.508 mm).

SIMULATION RESULTS AND DISCUSSION

In Figures 2a and 2b the spatial distributions of the pressure and the acoustic energy density along the sound path (thickness direction of the layers) are shown for all considered constructions (all combinations of transmission layer and reflector thicknesses with $\lambda/4$ and $\lambda/2$ water layer thicknesses, respectively). For these calculations it was assumed that the electrodes of the piezoceramic are connected to an electric generator with a source voltage amplitude of 1 V and a source resistance of 50 Ω . Since on the free outer surface of the reflector there is always a pressure node, for all constructions xy0 and xyH (x and y are any codes for the transmission layer and the reflector layer thickness, respectively) there is also a pressure node at the right boundary of the water layer. For a water layer thickness of $\lambda/2$ (codes xH0 and xHH) there is an additional pressure node at the other boundary (interface between layers B and C). A pressure node in the middle of the water layer can only occur for a $\lambda/2$ water layer combined with a $\lambda/4$ reflector layer (code xHQ). As can be seen from the pressure scales, high values of pressure are obtained particularly in cases where the total acoustic path length is a multiple of $\lambda/2$ (these are OQQ, QQ0, QQH, HQQ in Fig. 2a and OH0, OHQ, HH0, HHH in Fig. 2b).

The acoustic energy density in the water layer is also dependent on the reflector thickness. For a reflector thickness of $\lambda/2$ (codes xyH), the acoustic energy density is much higher in the reflector than in the adjacent water layer, because for these geometries the displacement amplitudes have the same maximum value in both layers. This follows from the condition of continuity for the displacement that must apply at the water-reflector interface. In Figs. 3a and 3b the frequency spectra of the acoustic energy density in the water layer for all considered constructions are shown. As for Fig. 2, a source voltage amplitude of 1 V and a source resistance of 50 Ω were assumed. Since the electric impedance of the multilayer systems is strongly dependent on frequency, the voltage at the piezoceramic, as well as the total electric input energy to the system, also vary with frequency. Therefore, these figures alone are not sufficient to predict the efficiency of a particular construction. For the piezoceramic's resonance frequency of 3 MHz, the acoustic energy density in the water layer shows maxima for all designs with a total acoustic path length that equals a multiple of $\lambda/2$ at 3 MHz (OQQ, QQ0, QQH, HQQ in Fig. 3a, OH0, OHQ, HH0 in Fig. 3b). Although this condition is not fulfilled for the designs OQH and HQH (Fig. 3a), the results look very similar to the spectra for OQQ and HQQ, respectively. However, this similarity is not a basic property of these

- 3 -

designs but is due to a smoothing effect on the energy density spectra that is caused by the 50 Ω source resistance in series with the piezoelectric structure. To illustrate this effect, in the upper right picture of Fig. 3a (design OQH) the respective energy density spectrum for a zero source resistance is included (black curve). This curve shows a double peak, which is characteristic for designs where the total acoustic path length at 3 MHz does *not* match a multiple of $\lambda/2$.

Other designs that do not fulfill the wavelength criterion can be identified in Figs. 3a and 3b. These designs either show a double peak near 3 MHz (QQQ, HQQ, OHQ, QHH, HHQ) or peaks far below and above 3 MHz but not near the piezoceramic's fundamental (QQQ, QHQ). Finally, the designs OHH and HHH (Fig. 3b) show only very small maxima at 3 MHz, surrounded by two greater peaks

below and above 3 MHz, respectively, although they fulfil the wavelength criterion at 3 MHz. However, the peak at 3 MHz is smoothed out due to the effect of the driving source resistance which at 3 MHz is large compared to the resonator impedance.

Similar results for node positions and spectra have been obtained, although with altered peak magnitudes, when carbon (speed of sound 4260 m/s, mass density 1470 kg/m³) or silicon (speed of sound 8430 m/s, mass density 2340 kg/m³) were used in the simulations.

CONCLUSION

The discussed series of designs describe constructions which can be chosen to position particles either at a wall or centrally within a chamber. Moving particles from the centre of a chamber to the chamber walls is also possible by a change in frequency. In particular, this can be achieved in chambers OHH or HHH. Particles may be also moved from one wall to the other. With respect to system efficiency, it is advantageous to operate near the piezoceramic's fundamental resonance. Nonetheless, other operating frequencies may produce some useful systems.

- 4 -

CLAIMS

1. Apparatus for directing particles entrained in a fluid, comprising a chamber having a first wall comprising a material capable of generating a sound wave and a second, opposite wall capable of reflecting the sound wave in which the first and second walls define a conduit for the passage of the fluid and in which the frequency ν of the sound wave, the thickness of the first and second walls and the width of the conduit are selected so as provide for the generation of a standing sound wave having a pressure node in the fluid at or adjacent the first and/or second wall of the chamber or the centre of the conduit.
2. Apparatus according to Claim 1, in which the first wall further comprises a material capable of transmitting the sound wave.
3. Apparatus according to Claim 1 or Claim 2, in which the thickness of the second wall is a multiple of $\lambda_2/4$ or $\lambda_2/2$ for the wavelength λ_2 of the sound wave therein and the width of the conduit is a multiple of $\lambda_1/2$ or $\lambda_1/4$ for the wavelength of the sound wave λ_1 in the fluid.
4. Apparatus according to Claim 3 when dependant on Claim 2, in which the thickness of the material transmitting the sound wave in the first wall is a multiple of $\lambda_1/2$ or $\lambda_1/4$ of the wavelength of the sound wave therein λ_1 .
5. Apparatus according to any of Claims 1 to 4, in which the thickness of the material capable of generating the sound wave is a multiple of $\lambda_g/2$ of the wavelength of the sound wave therein λ_g .

- 5 -

6. Apparatus according to any preceding Claim, in which the total acoustic path length of the wave is a multiple of $\lambda_f/2$ of the wavelength of the sound wave λ_f in the fluid.

7. Apparatus according to any preceding Claim, in which the material capable of generating the sound wave is a piezoceramic material.

8. Apparatus according to Claim 7, in which the frequency ν of the sound wave is at or adjacent the resonant frequency of the piezoceramic material.

9. Apparatus according to any preceding Claim, in which the second wall comprises steel, carbon or silicon.

10. Apparatus according to any preceding Claim, in which the material in the first wall capable of transmitting the sound wave comprises steel, carbon or silicon.

11. Apparatus according to any preceding Claim, further comprising a sensor capable of detecting the particles.

12. Apparatus according to Claim 11, in which the sensor comprises an optical biosensor.

13. Apparatus according to any preceding Claim, in which the sound wave is an ultrasound wave.

- 6 -

14. Apparatus substantially as hereinbefore described with reference to, and as shown in, the accompanying drawings.

15. A method of detecting particles in a fluid comprising the steps of i) passing the fluid through a chamber having a first wall comprising a material capable of generating a sound wave and a second, opposite wall capable of reflecting the sound wave in which the first and second walls define a conduit for the passage of the fluid and in which, for a given wavelength of the sound wave, the thickness of the first and second walls and the width of the conduit are selected so as to provide for the generation of a standing sound wave having a pressure node in the fluid at or adjacent the first and/or second wall of the chamber or the centre of the conduit, ii) generating the sound wave and iii) detecting the particles within or shortly after they emerge from the conduit.

16. A method according to Claim 15, in which the sound wave is an ultrasound wave.

17. Use of apparatus according to any of Claims 1 to 14, for the detection of the presence or extent of a target bacteria in a fluid.

- 7 -

ABSTRACT

Ultrasound standing wave radiation acts on suspensions, emulsions, and colloids to drive the dispersed particles (solid particles, bubbles, or oil droplets) towards either nodal or anti-nodal positions in the sound field. Using narrow chambers which contain only one nodal plane we have been able to position this pressure node at: 1) The reflector side wall of a chamber, this has been used to draw cells to a surface for detection by a biosensor. 2) The centre of the chamber, this has been combined with manipulation by laminar flow to produce a filter to remove contaminating particles. These systems have been developed using a one-dimensional transfer matrix model to predict the node positions and the acoustic energy density in the fluid. The model has been further used to predict chamber designs in which pressure nodes are at 1) the transducer side wall of the chamber and 2) both walls of the chamber.

SECRETARY OF STATE

1/5

Fig. 1 Schematic representation of the acoustic chamber (4-layer system): A piezoelectric, B stainless steel transmission layer, C water layer, D stainless steel reflector layer.



2/5





Fig. 2a Distributions of pressure (scale in kPa on the left) and acoustic energy density (scale in J/m^2 on the right) along the sound path at 3 MHz for all 9 possible constructions for a chamber with a water layer of 0.126 mm and 0.14 mm or 0.172 mm stainless steel transmission and reflector layers. Pressure drops to 0 at the node positions. Layer boundaries are indicated by vertical black lines. Results are valid for an electric drive generator with a source voltage amplitude of 1 V and a source resistance of 50 Ω . Scale on the horizontal axis (sound path) is given in mm.

3/5



NOT TO BE AMENDED

4/5




Fig. 3a Frequency spectra of the acoustic energy density (in J/m³) within the water layer for all 9 possible chambers with a water layer of $\lambda/4$ (0.125 mm) and 0, $\lambda/4$ or $\lambda/2$ stainless steel transmission and reflector layers (the thickness values given in fractions of the acoustic wavelength correspond to a frequency of 1 MHz). Results are valid for an electric drive generator with a source voltage amplitude of 1 V and a source resistance of 50 Ω. The upper right picture additionally shows the result for a zero source resistance (black curve). Scale on the horizontal axis (frequency) is given in MHz.

SECRET

s/s




Fig. 3b The same as Fig. 3a but with a water layer of $\lambda/277\lambda_0, 2577\text{mm}$ and $770, 772.4$ or $\lambda/2$ stainless steel transmission and reflection layers.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.